

Outdoor

Low

Low shoes



### The +

- \*Shaped cleats: adherence. and gripping on rough floors
- \*Grooves for liquid and mud dispersement.
- \*Raised heel 1 cm and lateral edges: reinforced grip on ladders.
- \*TPU outsole: strength and durability.
- \*Front and back reinforcements.

### PURCHASE PACKAGING

Référence	Taille	Carton
9STL370035	35	6
9STL370036	36	6
9STL370037	37	6
9STL370038	38	6
9STL370039	39	6
9STL370040	40	6
9STL370041	41	6
9STL370042	42	6
9STL370043	43	6
9STL370044	44	6
9STL370045	45	6
9STL370046	46	6
9STL370047	47	6
9STL370048	48	6

### DESCRIPTION

STONE is a formidable efficiency safety shoe. Specially designed for construction industry, STONE benefits from a PU / TPU sole resistant to abrasion, oils and hydrocarbons and equipped with prominent grips. Its pull-up leather upper has good waterproofing. STONE features a toe-cap and an anti-penetration plate made of composite for optimal protection. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration.

### SECTORS

Mining

Extracting Oil and Gas

Energy

Infrastructure, building industry

## TECHNICAL FEATURES

<b>Color</b>	Brown	<b>Lining</b>	Breathable 3D mesh
<b>Upper</b>	Cuir pull-up		
<b>Toecap</b>	Composite		
<b>Puncture resistant sole</b>	Textile		
<b>Midsole</b>	PU		
<b>Outsole</b>	TPU		
<b>Insole</b>	Removable, perforated EVA		
<b>Main assembly</b>	Injected		
<b>Closing</b>	Lacing closure		

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)



EN ISO 20345:2011

S3

SRC

## EPI CAT. I

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe  $0,1M\Omega < A < 1000 M\Omega$  + Fuel and oil resistant contact outsole + Energy absorbing heel  $E \geq 20$  Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP