

Ref. **9CYR100**

Specialties

Low

Low shoes



O1



The +

*PU2D injected outsole: comfort and adherence.

*Defined heel: safety on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9CYR100036	36	6
9CYR100037	37	6
9CYR100038	38	6
9CYR100039	39	6
9CYR100040	40	6
9CYR100041	41	6
9CYR100042	42	6
9CYR100043	43	6
9CYR100044	44	6
9CYR100045	45	6
9CYR100046	46	6
9CYR100047	47	6
9CYR100048	48	6
9CYR100049	49	6

Some sizes may only be available in certain countries

TECHNICAL FEATURES

Color	Black	Defined heel
Weight	410 g	
Upper	Full grain leather	
Midsole	PU	
Outsole	PU	
Insole	Textile and foam, removable	
Front bumper		
Lining	Breathable 3D mesh	

INSTRUCTION FOR USE AND STORAGE

Instructions for use

Storage instructions

Washing instructions

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21004368

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20347:2012

O1

SRC

Working shoes

O1 Minimal properties (=résistance to friction, tearing and slip resistance, water vapor permeability)+closed heel area +energy absorption in the heel area (E) + antistatic properties (A)

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol