



Cosmo

Superior fire tested doormat for busy entrances



- · Hardwearing polyamide carpet surface doormat.
- Suitable durability for high traffic entrance areas.
- Fibres scrape and wipe moisture from footwear for effective floor protection.
- Fully fire tested see datasheet for details.
- Anti-slip vinyl backing helps maintain mat position, even on smooth floors.
- UV and temperature resistant from 0°C to 60°C.





Styles Available







Grey/Brown



Grey/Black

Parts

Part Number	Size	Colour	Weight (kg)
CSM010601	0.6 m x 0.9 m	Grey/Black	1.9
CSM010602	0.9 m x 1.5 m	Grey/Black	4.7
CSM010604	1.2 m x 1.8 m	Black/Grey	7.1

Technical Specifications

Material	PA
Backing	Vinyl
Product Height	8 mm
Product Weight	3.5 kg / m ²

Part Number	Size	Colour	Weight (kg)
CSM060501	0.6 m x 0.9 m	Grey/Brown	1.9
CSM060502	0.9 m x 1.5 m	Grey/Brown	4.7
CSM060504	1.2 m x 1.8 m	Grey/Brown	7.1
CSM060701	0.6 m x 0.9 m	Grey/Beige	1.9
CSM060702	0.9 m x 1.5 m	Grey/Beige	4.7
CSM060704	1.2 m x 1.8 m	Grey/Beige	7.1

Min. Operating Temperature	0°C
Max. Operating Temperature	+60°C
Environmental Resistance	Suitable for indoor environments only
UV Resistance	Yes
Typical Applications	Entrance areas
Installation Method	Loose lay
Fire Tested to	Flame retardant to Cfl-S1.
COO (Country of Origin)	BE
Coating Thickness	2 mm
Tuft density	110,000 / m ²
Manufacturing process	Tufting 5/32'

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com www.cobaeurope.com