

Ref. 9SAP120

Multipurpose

Low

Low shoes



The +

- *Lightness.
- * Flexibility.
- * Comfort of use (insole foam HI-POLY + midsole EVA).
- * Dynamic profile and degraded two-tone outsole.

PURCHASE PACKAGING

Ref.	Size	Carton
9SAP120038	38	6
9SAP120039	39	6
9SAP120040	40	6
9SAP120041	41	6
9SAP120042	42	6
9SAP120043	43	6
9SAP120044	44	6
9SAP120045	45	6
9SAP120046	46	6
9SAP120047	47	6

Some sizes may only be available in certain countries

DESCRIPTION

Inspired by the design of running sneakers, the SAPHIR model seduces with its sleek look.

Metal-free, SAPHIR has been designed to offer the wearer lightness, flexibility and breathability.

The emphasis is on comfort: composite toe cap, textile anti-perforation midsole and Hi-Poly foam sockliner with cushions.

The nitrile rubber outsole, non-slip on metal and steel floors, is also resistant to hydrocarbons and heat.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Insole	HI-POLY foam
Color 2	Blue	Reinforcement material	TPU
Weight	497 g	Reinforcement location	Front
Upper	Polyester mesh	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB20013172

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2\A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)