

Ref. 6PHW200

### Vented Helmet General Use



### The +

#### PERFORMANCE

- High resistance level (lateral deformation(LD), low temperature - 30°C)
- ABS Shell

#### COMFORT

- Side ventings
- Integrated safety glasses
- Good fitting and lightweight feeling (head balance)
- Easy adjustment by ratchet
- Wide field of vision thanks to the short peak
- 3D textile sweatband

#### LIGHTWEIGHT

- 450g

Compatible with badge holder (6POBA) and earmuffs (6MX3000NSI)

#### DESCRIPTION

PHOENIX WIND Safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, side ventings, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 points chinstrap as a standard

#### SECTORS

Heavy & process industries

Mechanicals constructions

Light Industries

Regional/public authorities

Infrastructure, building industry

#### APPLICATIONS

Construction site, building and public works, industry...

#### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHW200NSI	-		16

#### SALES PACKAGING



Individual polybag

See also

## TECHNICAL FEATURES

Shape	Safety helmet	Color	Blue
Weight	450g	Color 2	Black
Shade	Clear	Features	ABS Shell LDPE 6 points harness Size adjustment from 52 to 63 cm
Harness features	6 points harness made of polyethelene 6 textile webbings	Service life	Manufacturing date indicated under the peak Shelf life: Storage for 2 years in standard conditions Use for 5 years in good conditions
Main risk	Prevention from falling objects and head injuries or head trauma	Adjustment	Adjustment by ratchet from 52 to 63 cm
Shell material	ABS		

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2314

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



EPI CAT. II

EN166:2001

Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)

EN397:2012 + A1:2012

Industrial safety helmets

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.

RETAILER STAMP